



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: PLID Thin Film Aerosol

Product use: Corrosion inhibitor / penetrant / lubricant for marine environments – for non-ferrous or ferrous as well as dissimilar metals / wherever there is excessive moisture

Supplier: Not available.

Manufacturers Name: Ship-2-Shore

109-7337 North Fraser Way
Burnaby, BC V5J 0G7
Canada

Telephone: 800-430-1533

Emergency Telephone: 866-836-8855

SECTION 2 — HAZARD IDENTIFICATION

WHMIS Classification

Compressed gas: Class A
Flammable and combustible: Class B5
Poisonous and Infectious Material: Class D2B

OSHA Hazards

Flammable Aerosols: Category 2
Carcinogenicity: Category 1B

GHS Label elements, including precautionary statement

Signal Word

Danger

Hazard statement(s)

H222: Extremely flammable aerosol.
H229: Causes damage to organs through prolonged or repeated exposure.
H336: May cause drowsiness or dizziness.

Precautionary statement(s)

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
P243: Take precautionary measures against static discharge.
P251: Do not pierce or burn, even after use.
P260: Do not breathe gas.
P264: Wash thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.

Label element



Response

Get medical advice/attention if you feel unwell.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

HMIS Classification

Health hazard	1
Flammability	4
Physical hazard	0

Potential health effects

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation.
Skin	Contact may result in irritation (redness and itching).
Eyes	Direct contact with eyes may cause irritation cause irritation to sever damage if left untreated.
Ingestion	Expected to be a low ingestion hazard. Irritation of mucus membranes of mouth, throat, esophagus and stomach along with nausea may occur.

SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

Compound	CAS-No.	Concentration (%wt)
Propane	74-98-6	10-30
Isobutane	775-28-5	5-10
Kerosene	8008-20-6	3-7
Mineral Spirits	8052-41-3	3-7
Other compounds below reportable levels*	Not available.	60-80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 4 — FIRST AID MEASURES

General advice

If negative symptoms developed while handling the product move out of the area to prevent further exposure. Consult a physician as a precautionary measure. If symptoms developed after being exposed to the material without proper protection. Show this safety data sheet to the doctor in attendance.

If inhaled

In emergency situations, use proper respiratory protection and immediately remove the affected person from exposure. Keep at rest. Administer artificial respiration if breathing has stopped. Seek medical attention.

In case of skin contact

Wash exposed skin thoroughly with soap and water. Cold water washing is suggested if irritation is caused by exposure. If irritation develops and is prolonged and/or sore, consult a physician.

In case of eye contact

Flush eyes with plenty of water for at least 15 minutes. Avoid rubbing the eye. If experiencing prolonged irritation or soreness, seek medical attention.

If swallowed

Do not induce vomiting. Rinse mouth well with water. Never give anything by mouth to an unconscious person. Seek medical attention.

Most important symptoms/effects, acute and delayed

Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 5 — FIRE FIGHTING MEASURES

Conditions of flammability

Open flame, high heat, and static discharge.

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Firefighting equipment/instructions

In case of fire, stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Hazardous combustion products

Not available.

Explosion data – sensitivity to mechanical

Not available.

Explosion data – sensitivity to static discharge

Not available.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 6 — ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Method and materials for containment and cleaning up

Land spill: Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see Section 13 of the SDS.

SECTION 7— HANDLING AND STORAGE

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

Component	CAS-No.	Type	Value	Basis
Propane	76-98-6	TWA	1000 ppm	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
		TWA	1000 ppm	
		TWAEV	1000 ppm 1800 mg/m ³	
Isobutane	75-28-5	STEL	1000 ppm	US. ACGIH Threshold Limit Values Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
		STEL	1000 ppm	
		TWA	800 ppm	
Kerosene	8008-20-6	TWA	200 mg/m ³	US. ACGIH Threshold Limit Values Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)
Mineral Spirits	8052-41-3	TWA	100 ppm	US. ACGIH Threshold Limit Values Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)
		TWA	572 ppm	
		STEL	580 mg/m ³	
		TWA	290 mg/m ³	
		TWA	100 ppm	
		TWA	525 mg/m ³	

Biological limit values: No biological exposure limits noted for the ingredient(s).

Exposure guidelines:

Canada - Alberta OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

Canada - Ontario OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

Personal Protection Equipment

Respiratory protection

If permissible levels are exceeded, use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

Skin/hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Long sleeved clothing and full length pants should be worn if repeated or prolonged direct contact is likely to occur.

Eye protection

If contact is likely, safety glasses with side shields or goggles should be worn. When using eye protection, equipment should be tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Specific engineering control

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Other

Wear suitable protective clothing. Use of an impervious apron is recommended.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form Aerosol. Compressed gas.
Color Not available.

Safety data

Odour Fresh Scent/Petroleum-like.
Odour threshold Not available.
pH Not available.
Melting point/Freezing point Not available.
Initial boiling point/boiling range 212°F (100°C) estimated.
Flash point < 23°C
Evaporation rate Not available.
Flammability (solid; gas) Not available.
Lower flammable/explosive limit 1.8 % estimated.
Upper flammable/explosive limit 9.5 % estimated.
Vapour pressure Not available.
Vapour density Not available.
Relative density 0.177 kg/L estimated.
Solubility Not available.
Partition coefficient - n-octanol/water Not available.
Auto-ignition temperature 860 °F (460°C) estimated.
Decomposition temperature Not available.
Viscosity Not available.
Heat of combustion (NFPA 30B) 40 kJ/g estimated.
Oxidizing properties Not oxidizing.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 10 — STABILITY AND REACTIVITY

Chemical stability

The product is stable and non-reactive under normal conditions of use, storage, and transport.

Possibility of hazardous reactions

Hazardous polymerization does not occur.

Materials to avoid

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Conditions to avoid

Heat and open flames. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Hazardous decomposition products

No hazardous decomposition products are known.

Reactivity

Material is stable under normal conditions.

SECTION 11 — TOXICOLOGICAL INFORMATION

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Dizziness.

Information on toxicological effects Acute toxicity

Component	Species	Test results
Propane (CAS#: 74-98-6) Acute Inhalation LC50	Mouse Rat	1237 mg/L, 120 Minutes 52%, 120 Minutes 1355 mg/L 658 mg/L/4h
Isobutane (CAS#: 75-28-5) Acute Inhalation LC50 LC50	Mouse Rat	1237 mg/L, 120 Minutes 52%, 120 Minutes 1355 mg/l
Kerosene (CAS#: 8008-20-6) Acute Dermal LD50	Rabbit	>2000 mg/kg >2000 mg/kg, 24 hr



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

Mineral Spirits (CAS#: 8052-41-3)		
Acute		
Dermal		
LD50	Rabbit	>2000 mg/kg
Oral		
LD50	Rat	>7500 mg/kg

* Toxicity data is presented for the individual components, in their pure form, and not as a mixture in their reported concentrations as in the product

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Germ cell mutagenicity

May cause genetic defects. No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

May cause cancer.

ACGIH Carcinogens

Kerosene (CAS 8008-20-6): A3 Confirmed animal carcinogen with unknown relevance to humans.

Canada - Manitoba OELs: carcinogenicity

Kerosene (non-aerosol), as total hydrocarbon vapor (CAS 8008-20-6): Confirmed animal carcinogen with unknown relevance to humans.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Not likely, due to the form of the product.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

Potential health effect

Not available.

Signs and symptoms of exposure

Not available.

Synergistic effect

Not available.

Additional information

Symptoms may be delayed.

SECTION 12 — ECOLOGICAL INFORMATION

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Ecotoxicity data

Kerosene (CAS#: 8008-20-6)

Fish	LC50	Pimephales Promelas Lepomis Macrochirus	45 mg/l, 96 hr 1740 mg/l, 96 hr
------	------	--	------------------------------------

Mineral Spirits (CAS#: 8052-41-3)

Algae	IC50	Pseudokrichneriella Subcapitata	3000 mg/l, 72 hr
-------	------	---------------------------------	------------------

Isobutane (CAS#: 75-28-5)

No ecological damage causes by this component.

Propane (CAS#: 74-98-6)

No ecological damage causes by this component.

Precedence and degradability

No data is available on the degradability of this product.

Bioaccumulation potential

No data available.

Partition coefficient n-octanol / water (log Kow)

Isobutane (CAS#: 75-28-5)	2.76
Mineral Spirits (CAS#: 8052-41-3)	3.16 - 7.15
Propane (CAS#: 74-98-6)	2.36
Kerosene (CAS#: 8008-20-6)	3.3 - >6.0

Mobility in soil

Not available.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

PBT and vPvB

Not available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13 — DISPOSAL CONSIDERATIONS

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

SECTION 14 — TRANSPORT INFORMATION

TDG

UN number

UN1950

UN proper shipping name

AEROSOLS, flammable.

Transport hazard class(es):

Class

2.1

Subsidiary risk

-

Packing group

Not applicable.

Environmental hazards

No environmental hazards.



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

ERG Code

10L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number

UN1950

UN proper shipping name

AEROSOLS, flammable.

Transport hazard class(es):

Class

2.1

Subsidiary risk

-

Label(s)

2.1

Packing group

Not applicable.

Environmental hazards

Does not cause environmental hazards.

ERG Code

10L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number

UN1950

UN proper shipping name

AEROSOLS

Transport hazard class(es):

Class

2.1



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

Subsidiary risk

-

Labels

None.

Packing group

Not applicable.

Environmental hazards:

Marine pollutant

Not a marine pollutant.

EMS

F-D, S-D

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

IATA; IMDG; TDG



General Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

SECTION 15 — REGULATORY INFORMATION

Canadian regulations:

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

109-7337 North Fraser Way Burnaby, BC V5J 0G7 Canada

T: 1-800-430-1533 www.ship2shore.com



SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

Precursor Control Regulations

Not regulated.

International regulations Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories:

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).



SHIP 2 SHORE
CORROSION PREVENTIVE COATINGS

SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

SECTION 16 — OTHER INFORMATION

Prepared July 18th, 2019. The information, recommendations, and suggestions in the safety data sheet, have been compiled from tests and data believed to be reliable. The above information is believed to be correct, but is not under guarantee or warranty to be all inclusive and shall be used only as a guide. The information contained herein is based on the present state of our knowledge and is only applicable to the product or material set forth in Section 1. The information provided may not be applicable or complete if such product material is used in combination with any other product or material, or in any process. The information provided on the product or material is with regard to appropriate safety precautions and does not represent any guarantee of the properties of the product. It is the user's obligation to determine the safety, toxicity and suitability for their own use of the product described herein and to comply with all applicable laws and regulations. Ship-2-Shore and its affiliates not be held liable for any damage resulting from handling or from contact with the above product.

