



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 1 — CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Industrial Thick Film Aerosol

**Product use:** Corrosion inhibitor / penetrant / lubricant for marine environments – for non-ferrous or ferrous as well as dissimilar metals / wherever there is excessive moisture

**Supplier:** Not available.

**Manufacturers Name:** Ship-2-Shore

109-7337 North Fraser Way

Burnaby, BC V5J 0G7

Canada

**Telephone:** 800-430-1533

**Emergency Telephone:** 866-836-8855

### SECTION 2 — HAZARD IDENTIFICATION

**WHMIS Classification**

Compressed gas: Class A

Flammable and combustible: Class B5

Poisonous and Infectious Material: Class D2B

**OSHA Hazards**

Flammable Aerosols: Category 2

Carcinogenicity: Category 1B

**GHS Label elements, including precautionary statement**

**Signal Word**

Danger

**Hazard statement(s)**

H222: Extremely flammable aerosol.

H229: Causes damage to organs through prolonged or repeated exposure.

H336: May cause drowsiness or dizziness.

**Precautionary statement(s)**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

P243: Take precautionary measures against static discharge.

P251: Do not pierce or burn, even after use.

P260: Do not breathe gas.

P264: Wash thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area.

**Label element**



**Response**

Get medical advice/attention if you feel unwell.

109-7337 North Fraser Way Burnaby, BC V5J 0G7 Canada

T: 1-800-430-1533 www.ship2shore.com



# SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### HMIS Classification

|                 |   |
|-----------------|---|
| Health hazard   | 1 |
| Flammability    | 4 |
| Physical hazard | 0 |

### Potential health effects

|            |   |
|------------|---|
| Inhalation | May cause damage to organs through prolonged or repeated exposure by inhalation.  |
| Skin       | Contact may result in irritation (redness and itching).   |
| Eyes       | Direct contact with eyes may cause irritation cause irritation to sever damage if left untreated.   |
| Ingestion  | Expected to be a low ingestion hazard. Irritation of mucus membranes of mouth, throat, esophagus and stomach along with nausea may occur. |

### SECTION 3 — COMPOSITION/INFORMATION ON INGREDIENTS

| Compound                                    | CAS-No.        | Concentration (%wt) |
|---|----------------|---------------------|
| Propane                                     | 74-98-6        | 45-70               |
| Isobutane                                   | 775-28-5       | 15-40               |
| Distillated (petroleum), Hydrotreated Light | 64742-47-8     | 3-7                 |
| Kerosene                                    | 8008-20-6      | 1-5                 |
| Mineral Spirits                             | 8052-41-3      | 1-5                 |
| Other components below reportable levels*   | Not available. | 10-30               |

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 4 — FIRST AID MEASURES

#### General advice

If negative symptoms developed while handling the product move out of the area to prevent further exposure. Consult a physician as a precautionary measure. If symptoms developed after being exposed to the material without proper protection. Show this safety data sheet to the doctor in attendance.

#### If inhaled

In emergency situations, use proper respiratory protection and immediately remove the affected person from exposure. Keep at rest. Administer artificial respiration if breathing has stopped. Seek medical attention.

#### In case of skin contact

Wash exposed skin thoroughly with soap and water. Cold water washing is suggested if irritation is caused by exposure. If irritation develops and is prolonged and/or sore, consult a physician.

#### In case of eye contact

Flush eyes with plenty of water for at least 15 minutes. Avoid rubbing the eye. If experiencing prolonged irritation or soreness, seek medical attention.

#### If swallowed

Do not induce vomiting. Rinse mouth well with water. Never give anything by mouth to an unconscious person. Seek medical attention.

#### Most important symptoms/effects, acute and delayed

Prolonged exposure may cause chronic effects.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

#### General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 5 — FIRE FIGHTING MEASURES

#### Conditions of flammability

Open flame, high heat, and static discharge.

#### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

#### Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

#### Special protective equipment for fire-fighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

#### Firefighting equipment/instructions

In case of fire, stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

#### General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

#### Hazardous combustion products

Not available.

#### Explosion data – sensitivity to mechanical

Not available.

#### Explosion data – sensitivity to static discharge

Not available.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 6 — ACCIDENTAL RELEASE MEASURES

#### **Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

#### **Method and materials for containment and cleaning up**

**Land spill:** Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see Section 13 of the SDS.

### SECTION 7— HANDLING AND STORAGE

#### **Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe gas. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

#### **Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

**SAFETY DATA SHEET**

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

**SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION**

| Component                                   | CAS-No.               | Type  | Value                              | Basis  |
|---|-----------------------|-------|------------------------------------|--|
| Propane                                     | 76-98-6               | TWA   | 1000 ppm                           | Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)<br>Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)<br>Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)   |
|   |                       | TWA   | 1000 ppm                           |  |
|   |                       | TWAEV | 1000 ppm<br>1800 mg/m <sup>3</sup> |  |
| Isobutane                                   | 75-28-5               | STEL  | 1000 ppm                           | US. ACGIH Threshold Limit Values<br>Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)<br>Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)   |
|   |                       | STEL  | 1000 ppm                           |  |
|   |                       | TWA   | 800 ppm                            |  |
| Distillated (petroleum), Hydrotreated Light | 64742-47-8            | TWA   | 200 mg/m <sup>3</sup>              | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)  |
| Kerosene                                    | 8008-20-6             | TWA   | 200 mg/m <sup>3</sup>              | US. ACGIH Threshold Limit Values<br>Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)<br>Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)<br>Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)<br>Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)   |
| Mineral Spirits                             | 8052-41-3             | TWA   | 100 ppm                            | US. ACGIH Threshold Limit Values<br>Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)<br>Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)<br>Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)<br>Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)<br>Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) |
|   |                       | TWA   | 572 ppm                            |  |
|   |                       | STEL  | 580 mg/m <sup>3</sup>              |  |
|   |                       | TWA   | 290 mg/m <sup>3</sup>              |  |
|   |                       | TWA   | 100 ppm                            |  |
|   |                       | TWA   | 100 ppm                            |  |
| TWA   | 525 mg/m <sup>3</sup> |       |                                    |  |

**Biological limit values:** No biological exposure limits noted for the ingredient(s).



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### Exposure guidelines:

#### Canada - Alberta OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

#### Canada - British Columbia OELs: Skin designation

Distillated (petroleum), Hydrotreated Light (CAS 64742-47-8): Can be absorbed through the skin.

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

#### Canada - Manitoba OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

#### Canada - Ontario OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

#### Canada - Saskatchewan OELs: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

Kerosene (CAS 8008-20-6): Can be absorbed through the skin.

### Personal Protection Equipment

#### Respiratory protection

If permissible levels are exceeded, use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

#### Skin/hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. Long sleeved clothing and full length pants should be worn if repeated or prolonged direct contact is likely to occur.

#### Eye protection

If contact is likely, safety glasses with side shields or goggles should be worn. When using eye protection, equipment should be tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

#### Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### Specific engineering control

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### Other

Wear suitable protective clothing. Use of an impervious apron is recommended.

## SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

### Appearance

Form Aerosol. Compressed gas.  
Color Not available.

### Safety data

Odour Fresh Scent/Petroleum-like.  
Odour threshold Not available.  
pH Not available.  
Melting point/Freezing point Not available.  
Initial boiling point/boiling range 324.5°F (100°C) estimated.  
Flash Point (ASTM D93) < 23°C  
Evaporation rate < 1  
Flammability (solid; gas) Not available.  
Lower flammable/explosive limit 1.7 % estimated.  
Upper flammable/explosive limit 9.2 % estimated.  
Vapour pressure (ambient temp) 62 psig  
Vapour density Not available.  
Relative density (ASTM D1217-15) 0.876 kg/L  
Solubility (water) Completely miscible.  
Partition coefficient - n-octanol/water Not available.  
Auto-ignition temperature 860 °F (460°C) estimated.  
Decomposition temperature Not available.  
Viscosity at 25°C Not available.  
VOC Content 25% estimated.  
Heat of combustion (NFPA 30B) 40 kJ/g estimated.  
Oxidizing properties Not oxidizing.





**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 10 — STABILITY AND REACTIVITY

#### Chemical stability

The product is stable and non-reactive under normal conditions of use, storage, and transport.

#### Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### Materials to avoid

Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

#### Conditions to avoid

Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

#### Hazardous decomposition products

No hazardous decomposition products are known.

#### Reactivity

Material is stable under normal conditions.

### SECTION 11 — TOXICOLOGICAL INFORMATION

#### Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation. Dizziness.

| Component   | Species | Test results                               |
|---|---------|--|
| Propane (CAS#: 74-98-6)<br><b>Acute</b><br><b>Inhalation</b><br>LC50          | Mouse   | 1237 mg/L, 120 Minutes<br>52%, 120 Minutes |
|   | Rat     | 1355 mg/L<br>658 mg/L/4 hr                 |
| Isobutane (CAS#: 75-28-5)<br><b>Acute</b><br><b>Inhalation</b><br>Gas<br>LC50 | Mouse   | 1237 mg/L, 120 Minutes<br>52%, 120 Minutes |
|   | Rat     | 1355 mg/L                                  |



# SHIP 2 SHORE

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

|   |                                     |   |
|---|-------------------------------------|---|
| Distillates(petroleum), Hydrotreated Light<br>(CAS#: 64742-47-8)<br><b>Acute</b><br><b>Dermal</b><br>LD50<br><br><b>Inhalation</b><br>LC50<br><br><b>Oral</b><br>LD50 | Rabbit<br><br>Rat<br><br>Rat        | >2000 mg/kg<br>>2000 mg/kg, 24 hr<br><br>>7.5 mg/L, 6 hr<br>>4.6 mg/L, 4 hr<br><br>>5000 mg/kg                                      |
| Kerosene (CAS#: 8008-20-6)<br><b>Acute</b><br><b>Dermal</b><br>LD50<br><br><b>Inhalation</b><br>LC50<br><br><b>Oral</b><br>LD50                                       | Rabbit<br><br>Cat<br>Rat<br><br>Rat | >2000 mg/kg<br>>2000 mg/kg, 24 hr<br><br>>6.4 mg/L, 6 hr<br>>7.5 mg/L, 6 hr<br>>4.3 mg/L, 4 hr<br>>0.1 mg/L, 8 hr<br><br>>5000mg/kg |
| Mineral Spirits (CAS#: 8052-41-3)<br><b>Acute</b><br><b>Dermal</b><br>LD50<br><br><b>Oral</b><br>LD50   | Rabbit<br><br>Rat                   | >2000 mg/kg<br><br>>7500 mg/kg  |

\* Toxicity data is presented for the individual components, in their pure form, and not as a mixture in their reported concentrations as in the product

### Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

### Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

### Respiratory sensitization

Not a respiratory sensitizer.

### Skin sensitization



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

This product is not expected to cause skin sensitization.

### **Germ cell mutagenicity**

May cause genetic defects. No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

### **Carcinogenicity**

May cause cancer.

### **ACGIH Carcinogens**

Kerosene (CAS 8008-20-6): A3 Confirmed animal carcinogen with unknown relevance to humans.

### **Canada - Manitoba OELs: carcinogenicity**

Kerosene (non-aerosol), as total hydrocarbon vapor (CAS 8008-20-6): Confirmed animal carcinogen with unknown relevance to humans.

### **Reproductive toxicity**

This product is not expected to cause reproductive or developmental effects.

### **Specific target organ toxicity - single exposure**

Not classified.

### **Specific target organ toxicity - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

### **Aspiration hazard**

Not likely, due to the form of the product.

### **Chronic effects**

Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

### **Potential health effect**

Not available.

### **Signs and symptoms of exposure**

Not available.

### **Synergistic effect**

Not available.

### **Additional information**

Symptoms may be delayed.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

**SAFETY DATA SHEET**

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

**SECTION 12 — ECOLOGICAL INFORMATION**

**Ecotoxicity**

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

**Ecotoxicity data**

Distillates(petroleum), Hydrotreated Light (CAS#: 64742-47-8)

|      |      |   |                 |
|------|------|---|-----------------|
| Fish | LC50 | Rainbow trout, Donaldson trout<br>(Oncorhynchus mykiss) | 2.9 mg/l, 96 hr |
|------|------|---|-----------------|

Kerosene (CAS#: 8008-20-6)

|      |      |  |                                    |
|------|------|--|------------------------------------|
| Fish | LC50 | Pimephales Promelas<br>Lepomis Macrochirus | 45 mg/l, 96 hr<br>1740 mg/l, 96 hr |
|------|------|--|------------------------------------|

Mineral Spirits (CAS#: 8052-41-3)

|       |      |                                 |                  |
|-------|------|---------------------------------|------------------|
| Algae | IC50 | Pseudokrichneriella Subcapitata | 3000 mg/l, 72 hr |
|-------|------|---------------------------------|------------------|

Isobutane (CAS#: 75-28-5)

No ecological damage causes by this component.

Propane (CAS#: 74-98-6)

No ecological damage causes by this component.

**Precedence and degradability**

No data is available on the degradability of this product.

**Bioaccumulation potential**

No data available.

**Partition coefficient n-octanol / water (log Kow)**

|  |             |
|--|-------------|
| Isobutane (CAS#: 75-28-5)                  | 2.76        |
| Mineral Spirits (CAS#: 8052-41-3)          | 3.16 - 7.15 |
| Propane (CAS#: 74-98-6)                    | 2.36        |
| Distillates(petroleum), Hydrotreated Light | 5.1-8.8     |
| Kerosene (CAS#: 8008-20-6)                 | 3.3 - >6.0  |

**Mobility in soil**

Not available.

**PBT and vPvB**

Not available.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13 — DISPOSAL CONSIDERATIONS

### Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Local disposal regulations

Dispose in accordance with all applicable regulations.

### Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

### Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

### Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

## SECTION 14 — TRANSPORT INFORMATION

### TDG

#### UN number

UN1950

#### UN proper shipping name

AEROSOLS, flammable.

#### Transport hazard class(es):

##### Class

2.1

#### Subsidiary risk

-

#### Packing group

Not applicable.

#### Environmental hazards

No environmental hazards.

#### ERG Code

10L



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. This product meets the exemption requirements and may be shipped as a limited quantity.

### IATA

#### UN number

UN1950

#### UN proper shipping name

AEROSOLS, flammable.

#### Transport hazard class(es):

##### Class

2.1

#### Subsidiary risk

-

#### Label(s)

2.1

#### Packing group

Not applicable.

#### Environmental hazards

Does not cause environmental hazards.

#### ERG Code

10L

### Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

#### Other information

##### Passenger and cargo aircraft

Allowed with restrictions.

##### Cargo aircraft only

Allowed with restrictions.

### IMDG

#### UN number

UN1950

#### UN proper shipping name

AEROSOLS

#### Transport hazard class(es):

##### Class

2.1

#### Subsidiary risk

-



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### Labels

None.

### Packing group

Not applicable.

### Environmental hazards:

#### Marine pollutant

Not a marine pollutant.

### EMS

F-D, S-D

### Special precautions for user

Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable.

### IATA; IMDG; TDG



### General Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

## SECTION 15 — REGULATORY INFORMATION

### Canadian regulations:

#### Controlled Drugs and Substances Act

Not regulated.

#### Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### Greenhouse Gases

Not listed.

#### Precursor Control Regulations

Not regulated.



**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

**SAFETY DATA SHEET**

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

**International regulations Stockholm Convention**

Not applicable.

**Rotterdam Convention**

Not applicable.

**Kyoto protocol**

Not applicable.

**Montreal Protocol**

Not applicable.

**Basel Convention**

Not applicable.

**International Inventories:**

| Country(s) or region        | Inventory name   | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia                   | Australian Inventory of Chemical Substances (AICS)                     | No                     |
| Canada                      | Domestic Substances List (DSL)   | Yes                    |
| Canada                      | Non-Domestic Substances List (NDSL)                                    | No                     |
| China                       | Inventory of Existing Chemical Substances in China (IECSC)             | No                     |
| Europe                      | European Inventory of Existing Commercial Chemical Substances (EINECS) | No                     |
| Europe                      | European List of Notified Chemical Substances (ELINCS)                 | No                     |
| Japan                       | Inventory of Existing and New Chemical Substances (ENCS)               | No                     |
| Korea                       | Existing Chemicals List (ECL)  | No                     |
| New Zealand                 | New Zealand Inventory  | No                     |
| Philippines                 | Philippine Inventory of Chemicals and Chemical Substances (PICCS)      | Yes                    |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory                          | Yes                    |

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).





**SHIP 2 SHORE**

CORROSION PREVENTIVE COATINGS

## SAFETY DATA SHEET

Emergency Telephone: 1-866-836-8855

WWW.SHIP-2-SHORE.COM

### SECTION 16 — OTHER INFORMATION

Prepared July 19<sup>th</sup>, 2019. The information, recommendations, and suggestions in the safety data sheet, have been compiled from tests and data believed to be reliable. The above information is believed to be correct, but is not under guarantee or warranty to be all inclusive and shall be used only as a guide. The information contained herein is based on the present state of our knowledge and is only applicable to the product or material set forth in Section 1. The information provided may not be applicable or complete if such product material is used in combination with any other product or material, or in any process. The information provided on the product or material is with regard to appropriate safety precautions and does not represent any guarantee of the properties of the product. It is the user's obligation to determine the safety, toxicity and suitability for their own use of the product described herein and to comply with all applicable laws and regulations. Ship-2-Shore and its affiliates not be held liable for any damage resulting from handling or from contact with the above product.

