

OD755

Timber Frame Tape

**Available in rolls of
50mm, 70mm & 100mm widths x 25 Metres**

OD755 is a composite PE resin cloth consisting of a Matt Black HDPE woven cloth, laminated between two layers of LDPE film and with an extremely high tack solvent acrylic adhesive on one side and supplied on a single sided kraft paper release liner.

High performance, repositionable, and able to be installed without the use of razor, knives or scissors makes OD755 a very user-friendly product. This tape has excellent UV stability, adhesive ageing characteristics and good adhesion to self. The high coat weight helps create a seal around fasteners that penetrate it.

Designed for the permanent protection of timber frame work under a decking. Applied to the frames before decking laid, it protects joists from rot and water ingress. Used as a flashing tape for permanent sealing of house wraps (particularly semi-permeable membranes) to building penetrations (primarily doors, windows and ventilation points). Designed to ensure that permanent moisture/vapour seals can be created, as required. Can also be used as a protective medium and for other sealing functions and as a patching and repair product to membranes like ground sheets, tarpaulins, taught liners etc.

The surfaces compatible with OD755 are:

- ♦ Most current building surfaces
- ♦ Concrete and coatings that contain hydraulic binders, tiles, bricks.
- ♦ Aluminium, metals, glass, wood (treated), PVC...

OD755 TIMBER FRAME
For long-term flashing, sealing & protection

Temperature
Range
-25°C to 90°C

- Protection of decking joists from rot
- Hand-tearable on a release liner, excellent UV stability

